

Product information

SUN OIL COMPANY (Belgium) N.V.

Technical Customer Service

INGBERTHOEVEWEG 4 - B2630 AARTSELAAR - Tel: +323/458.12.30 - Fax: +323/458.14.78



Super C euro SAE 15W40

Description Mixed fleet engine oil SAE 15W40, suitable for virtually all (including recent model) passenger cars, many light and heavy trucks and busses as well as for off-the-road and stationary equipment. Meets latest API and ACEA engine oils requirements.

Application For the lubrication of gasoline and diesel engines requiring an engine oil with one or more of the below mentioned API or ACEA specifications. This oil is particularly suitable for engines with EGR (= exhaust gas recirculation) systems and for most engines equipped with a NO_x reduction system (SCR).

Specifications

- API CI-4 / CH-4 / CG-4 / CF / SL
- ACEA A3 / B3 / B4 / E3 / E5 / E7
- MB 228.3 MB 229.1
- Cummins 20071/76/78 Cummins 20072/77
- MAN M3275 MACK EO-M & EO-M Plus
- Volvo VDS-3 VW 505.00
- Allison C-4 MTU Type II

Properties

- Improved dispersancy through highly effective additive technology.
- Greater protection against soot EGR induced wear and sludge formation.
- More effective use of TBN to neutralise extra EGR related acid.
- Offers both improved "bore polishing" and "corrosion" protection .
- Pistons and valves/valve trains keep extremely clean.
- Exhaust gas catalyst compatible.

Typical analysis :

- density at 15°C : 0.883
- viscosity at 40°C : 103 cSt
- viscosity at 100°C : 14.2 cSt
- viscosity at -20°C: <6500 cP
- viscosity index : 140
- flash point : 230°C
- pour point : -33°C
- T.B.N. : 10.2 mg KOH/g
- colour : L3.0