

Product information

SUN OIL COMPANY (Belgium) N.V. Technical Customer Service
INGBERTHOEVEWEG 4 - B2630 AARTSELAAR - Tel: +323/458.12.30 - Fax: +323/458.14.78



Synturo Brilliant LongLife II SAE 0W30

- Description** Fully synthetic, long life, fuel economy engine oil for VW/Audi engines subjected to extended maintenance interval operation, according to "VW Norm 503.00/506.00/506.01".
- Application** In VW/Audi engines, both diesel (included are pump type injector models) and gasoline, of the latest (starting year 2000) generation, designed to operate under VW/Audi extended maintenance interval conditions, in Germany known as "WIV-System". (=Wartungsintervallverlängerung-System). Excepted among others are some Audi S and Audi TT models.
- Specifications** - ACEA A1 / B1
- VW 503.00 / 506.00 / 506.01.
- Properties** - longest possible oil drain intervals for almost all VW/Audi engines. (built after 1999)
- ideal lubrication during whole maintenance interval
- latest state of the art low friction additive technology for optimum energy/emission efficiency and improved environmental protection .
- low high temp. high shear visc. for even more extreme fuel economy
- excellent flow characteristics at very low temperatures for improved cold start capacity.
- high thermal stability and low volatility.

Sunoco's engine oil for VW-AUDI-SEAT-SKODA
model vehicles with "WIV-system" !!!

(for technical reasons, this oil is NOT to be recommended for other VW vehicles !)

Typical analysis :

- density at 15°C : 0.843
- viscosity at 40°C : 55.3 cSt
- viscosity at 100°C : 10.1 cSt
- viscosity at -35°C : <6200 cP
- viscosity index : 174
- flash point : 212°C
- pour point : -45 °C
- T.B.N. : 10 mg KOH/g
- colour : light
- volatility Noack : 12 %
- HTHS-visc. (150°C) : 3 cP