



# EVOLUTION SXR 5W-30



**Very high performance lubricant using ELF synthetics technology, « Fuel Economy », intended for all Gasoline and Diesel car engines.**

## APPLICATIONS

**All Gasoline and Diesel engines**

- Recommended for all Gasoline engines (multivalve, turbocharged, with or without catalytic converter) and all Diesel engines – with or without turbocharging – in cars and light vans

**Direct Injection**

- Particularly recommended to meet the enhanced requirements of direct injection Diesel engines

**The most severe journeys  
All times of year**

- Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions

**“Vigorous” driving**

- For all driving styles, particularly “vigorous” and high speeds

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

## PERFORMANCES

**International specifications**

ACEA 2004: A5/B5  
API: SL/CF

**OEMs approvals**

RENAULT Gasoline  
(except 2.0 16V Renault Sport, 2.0 T Renault Sport, V6 Renault Sport)

## CUSTOMER BENEFITS

**Fuel saving**

- Saves fuel. The average savings achieved are 6,5% (UTAC figures) in urban use and even more in cold weather

**Protecting the environment**

- Reduced pollutant emissions. Particle emissions are reduced by 15% on the average in urban use

**Very advanced  
Performance**

- Outstanding engine protection particularly against wear

**Extension of engine’s  
lifetime**

- Outstanding thermal stability and oxidation resistance, preventing any degradation even in very severe conditions

**Extension of out charge  
intervals**

- Elf Evolution SXR 5W30 has been engineered in order to comply with car manufacturers requirements in terms of extended oil charge intervals

## CHARACTERISTICS

ELF EVOLUTION SXR 5W-30	Method	Units	SAE Grade 5W-30
Density at 15°C	ASTM D1298	kg/m3	857
Viscosity at 40°C	ASTM D445	mm2/s	56,1
Viscosity at 100°C	ASTM 445	mm2/s	9,85
Viscosity Index	ASTM D2270	-	163
Pour Point	ASTM D97	°C	-45
Flash Point	ASTM D92	°C	236
T.B.N.	ASTM D2896	mgKOH/g	11,5

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS  
16, rue de la République  
92800 PUTEAUX  
1/1

Elf Evolution SXR 5W-30  
Version March 05  
MGP/03/05



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.