



TURBO DIESEL 15W-40



Multigrade oil developed by ELF, particularly intended to Diesel engines of light vehicles.

APPLICATIONS

All Diesel engines

- Recommended for the Diesel engines in cars and light vans.

All types of course

- Adapted to all types of course (in town, on highways and motorways) and during all times of year.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International specifications

ACEA A3 / B3
API SL / CF

CUSTOMER BENEFITS

Engine cleanliness

- Very good capacity to maintain the soots generated by the gas combustion in suspension. The engines is thus cleaner and its performances are preserved.

- Anti-wear and detergent properties, enabling the engine protection.

Lengthens engine life

- Elf Turbo Diesel 15W-40 answers to the quality system « European Engine Lubricant Quality Management System » (EELQMS), which guarantees the performance levels in a very rigorous way, and consequently the final quality of the lubricant.

CHARACTERISTICS

| ELF TURBO DIESEL 15W-40 | Units | SAE Grade 15W-40 |
|-------------------------|--------------------|------------------|
| Density at 15°C | kg/m ³ | 885 |
| Viscosity at 100°C | mm ² /s | 14,3 |
| Viscosity Index | - | 138 |
| Pour Point | °C | -33 |
| Flash Point | °C | 230 |
| B.N. | mgKOH/g | 8.2 |

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1

Elf Turbo Diesel 15W-40
Version July 05
MGP/07/05



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.