

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

Valvoline MaxLife Motor Oil

020/07

Valvoline MaxLife Motor Oil is a new synthetic blend motor oil, specially formulated to help meet the demands of “high-mileage” engines. Older engines tend to decrease in performance and increase oil consumption. Valvoline MaxLife Motor Oil with scientifically formulated additive system helps to slow down the aging process and maximize the life of your engine. Valvoline MaxLife is designed for passenger cars and light trucks with engines which have been running for more than 100.000 Km. MaxLife is not intended for real “Old Timer” models.

Performance levels	Viscosity Grade
API service SL/CF	10W-40
ACEA A3-02, B3-98 issue 2	10W-40
TüV-Certified	10W-40

Typical Properties	10W-40
Viscosity, mm ² /s @ 100 °C	14.2
Viscosity, mm ² /s @ 40 °C	98.5
Viscosity Index	150
Viscosity, mPa.s -25 °C	<7000
Sulphated Ash, wt. %	1.3
TAN; mg KOH/g (ASTM D-664)	2.5
TBN; mg KOH/g (ASTM D-2896)	10.4
Pour Point, °C	-36
Specific Gravity @ 15/15°C	0.880
Flash Point, COC, °C	218
Noack Evaporation wt%:	12.4

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Replaces:	Author's Initials:	Code
April 27, 2004	020/06	AdG	maxlife

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.