

# Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

## Valvoline SynPower XL-III SAE 5W-30

036/03

**Valvoline SynPower XL-III motor oil SAE 5W-30** is a premium LongLife III synthetic motor oil for Volkswagen Euro IV engines with DPF technology (Diesel Particle Filter). The product replaces the VW specifications 503.00, 506.00, 506.01 and is suitable for engines with WIV system, for extra long drain intervals up to 30.000 Km. or 2 years. SynPower XL-III SAE 5W-30 can be used in modern VW, AUDI, Seat and Skoda gasoline and diesel engines and gives excellent protection even under extreme circumstances. Can be mixed with all a.m. motor oils.

### The Valvoline SynPower XL-III motor oil advantages

- \* **Extended drain performance:** Suitable for long drain intervals according to VW/AUDI specifications.
- \* **Environment:** Suitable for EURO IV engines with Diesel Particle Filters
- \* **Fuel efficiency :** Enhanced fuel efficiency vs reference oil.
- \* **Storage and handling:** Less oil qualities, less containers, less mistakes; can be used where VW 503.00, 506.00, 506.01 are recommended.
- \* **Wear protection:** Excellent wear protection enhances engine life time.

Performance levels	SAE Viscosity Grade
ACEA A3/B4-04	5W-30
VW 504.00 (gasoline engines)	5W-30
VW 507.00 (diesel engines)	5W-30
Can be used where: VW 503.00, 506.00, 506.01 are specified.	5W-30

Typical Properties	5W-30
Viscosity, mm <sup>2</sup> /s @ 100 °C	11.5
Viscosity, mm <sup>2</sup> /s @ 40 °C	69.5
Viscosity Index	160
Viscosity, mPa.s -30°C	<6600
TBN; mg KOH/g	5.9
Pour Point, °C (ASTM D 97)	-42
Specific Gravity @ 15/15°C	0.850
Flash Point, COC, °C	226
HTHS viscosity	>3.5

**Note:** Valvoline SynPower XL-III SAE 5W-30 has been developed for modern engines which fall under the *extended oil drain system* prescriptions.

This information only applies to products manufactured in the following location(s): Europe

Effective Date:  
Oct. 25, 2005

Replaces:  
36/02

Author's Initials:  
AdG

*The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.*